

Datasheet: Premier 100% Polyester Thermal Insulation Range

Premier 100% Polyester Insulation is proudly manufactured in NZ from thermally bonded polyester fibres, for use in framed walls, ceilings, skillion roofs, suspended floors, and mid-floor applications in both residential and commercial construction and contains minimum 45% recycled fibre from post-consumer recycled PET plastic. Our Polyester Insulation is available in a range of widths and performance options and is available in blanket, skillion and segment forms.

	Nominal Thickness	Product Format	Standard Widths	Thermal Conductivity (Å 50/90)		
PREMIER 100% POLYESTER 70mm/90mm/140mm HIGH-DENSITY THERMAL INSULATION						
R1.8 70mm Wall	70mm	Segments	560mm	0.0368 W/mK		✓
R2.0 70mm Retro Wall	70mm	Segments	560mm			
R2.0 Segments	90mm	Segments	360mm/560mm	0.0371 W/mK	✓	✓
R2.2 Segments	90mm	Segments	360mm/560mm	0.0350 W/mK	✓	✓
R2.5 Segments	90mm	Segments	360mm/560mm	0.0345 W/mK	✓	✓
R2.6 Segments	140mm	Segments	360mm/560mm	0.0511 W/mK	✓	✓
R2.8 Segments	140mm	Segments	360mm/560mm	0.0441 W/mK	✓	✓
R3.2 Segments	140mm	Segments	360mm/560mm	0.0430 W/mK	✓	✓
R3.4 Segments	140mm	Segments	360mm/560mm	0.0412 W/mK	✓	✓
R3.6 Segments	140mm	Segments	360mm/560mm	0.0380 W/mK	✓	✓
PREMIER 100% POLYESTER THERMAL CEILING BLANKET						
R1.8 Ceiling Blanket	115mm	Roll Form	870mm	0.0524 W/mK	✓	✓
R2.4 Ceiling Blanket	145mm	Roll Form	870mm	0.0523 W/mK	✓	✓
R2.9 Ceiling Blanket	185mm	Roll Form	870mm	0.0581 W/mK	✓	✓
R3.3 Ceiling Blanket	200mm	Roll Form	870mm	0.0562 W/mK	✓	✓
R3.6 Ceiling Blanket	225mm	Roll Form	870mm	0.0590 W/mK	✓	✓
R3.8 Ceiling Blanket	225mm	Roll Form	870mm			
R4.1 Ceiling Blanket	245mm	Roll Form	870mm	0.0570 W/mK	✓	✓

Datasheet: Premier 100% Polyester Thermal Insulation Range

Nominal
Thickness

Product
Format

Standard
Widths

Thermal
Conductivity
(A 50/90)



PREMIER 100% POLYESTER HD MID-FLOOR / SKILLION ROOF SEGMENTS

	Nominal Thickness	Product Format	Standard Widths	Thermal Conductivity (A 50/90)	Eco Choice Aotearoa	BRANZ Appraised
R2.9 Mid-Floor-Skillion Segments	115mm	Segments	870mm	0.0385 W/mK		
R3.2 Mid-Floor-Skillion Segments	140mm	Segments	870mm	0.0430 W/mK	✓	✓
R3.4 Mid-Floor-Skillion Segments	140mm	Segments	870mm	0.0412 W/mK	✓	✓
R3.6 Mid-Floor-Skillion Segments	140mm	Segments	870mm	0.0380 W/mK	✓	✓
R3.2 Mid-Floor-Skillion Segments	165mm	Segments	870mm	0.0500 W/mK		
R3.6 Mid-Floor-Skillion Segments	165mm	Segments	870mm	0.0457 W/mK	✓	✓
R3.8 Mid-Floor-Skillion Segments	165mm	Segments	870mm	0.0400 W/mK	✓	✓

PREMIER 100% POLYESTER MASONRY WALL & SERVICE CAVITY INSULATION

R1.0 Wall & Service Cavity Blanket	45mm	Roll Form	580mm	0.0428 W/mK		
R1.3 Wall & Service Cavity Segments	45mm	Segments	360mm/560mm	0.0345 W/mK		

KEY FEATURES

- Manufactured using 100% polyester fibres and contains a minimum 45% post-consumer recycled PET plastics.
- Moisture and vermin resistant.
- Cost effective, flexible, and easy to install.
- Non-toxic, non-allergenic, non-irritant, soft and safe to touch.
- Proudly Made in NZ.
- Select products are BRANZ Appraised & Eco Choice Aotearoa Certified.
- 50 Year Durability Warranty.

NZBC COMPLIANCE

Premier Polyester is designed for thermal & acoustic insulation of buildings, when installed in accordance with the manufacturer's instructions, Premier 100% Polyester Insulation will perform for a minimum of 50 years, meeting the durability clause of NZBC B2.3.1(a). Premier Polyester meets the relevant clauses of NZBC E3 Internal Moisture, F2 Hazardous Building Materials, G6 Acoustic Design requirements and will support buildings to meet the H1 EnergyEfficiency H1.3.1(a) & H1.3.2.E.

Premier Polyester must be:

- Installed & maintained in a dry, protected environment.
- Installed in a building where provisions of NZBC E2 and E3 are met.
- Installed to the requirements of NZD 4226:2016: Energy Efficiency-Installing Bulk Thermal Insulation in Residential Buildings.

Datasheet: Premier 100% Polyester Thermal Insulation Range

NZBC C1-C6 PROTECTION FROM FIRE

All polyester insulation is classified as combustible insulating materials, and may therefore not be suitable for all applications, as stipulated in NZBC C-Production from Fire. We recommend you consult a Fire Engineer before specifying Polyester Insulation in buildings other than those described in Risk Group SH.

PIL Group Ltd polyester insulation has been tested to ISO 9705: 1993

Classification: Group 1-S
Smoke Production Rate: 1.0m²/s and therefore within the 5.0m²/s limit
Product Range: 100% Polyester up to 1,800gsm
Report Ref: BRANZ FC18133-01-2 (June 2024)

Classification: Group 3
Smoke Production Rate: 1.0m²/s and therefore within the 5.0m²/s limit
Product Range: 100% Polyester 1,800gsm up to 4,800gsm, including double-layer install
Report Ref: BRANZ FC18133-01-2 (June 2024)

IEC60695-11-5 Downlight Fire Standard

PIL Group Ltd Polyester Insulation has been tested and assessed as complying with IEC60695-11-5 Needle Flame Test.
Report Ref: Spectrum Lab Report No. 8616 (Aug 2023).

ENVIRONMENTAL

Premier Insulation is proud to carry Eco Choice Aotearoa Certification for selected Polyester Thermal & Acoustic Insulation products. All Premier 100% Polyester Insulation products are manufactured in the same environmentally considerate way. Eco Choice Aotearoa provides a credible and independent standard to guide people who want to purchase and use products that are proven to be better for the environment. At the foundation of Eco Choice Aotearoa are the technical specifications it develops, setting the most stringent, up to date standards for environmental compliance in business. New Zealand companies who meet or exceed these specification are permitted to display the ECA mark, widely recognised by New Zealanders as a badge of environmental leadership.

Eco Choice Aotearoa is internationally recognised as Level-A Eco-Label, and operates to internationally recognised standards and principles as a member of GEN, the Global Ecolabelling Network, which links a world of environmentally preferable products and services.

NZGBC GreenStar & HomeStar

Premier 100% Polyester Insulation can support a buildings ability to meet the GreenStar & HomeStar accreditation. The specification and use of Premier Polyester Insulation can support available 'points' for insulation materials. For specification or technical support, please contact our Technical Team on 0800 467 855 or email sales@premierinsulation.co.nz.

VOC EMISSIONS

PIL Group polyester insulation has been tested by CETEC Foray Ltd to ISO16000 Part 9:2011 with ISO16000 Part 11: 2011 "Determination of the emission of volatile organic compounds from building products and furnishing - Emission test chamber method" (Emission testing method for Greenguard UL 2818 certification program specification).

Report Reference: V2012043

VOC (C6 to C16) Emission Concentration: 0.007 mg/m³
Formaldehyde Emission Rate: <0.003ppm

All other Target CREL VOCs and their emission rates are well below the maximum allowable concentrations in accordance with Table 27A (revised December 30, 2014) of the standard method.

Datasheet: Premier 100% Polyester Thermal Insulation Range

POLYESTER MOISTURE ABSORPTION

Premier Polyester Insulation does not absorb or wick moisture. Tested at 50°C d 90% Relative Humidity for four days, showed moisture absorption of 0.00% by weight.

Testing was conducted by AWTA in accordance with ASTM C739-97 (Section 12 Modified)

Ref: 23-003634 (Sep 23).

NON-CORROSIVE & NON-HAZARDOUS

Polyester is considered non-corrosive and non-hazardous.

BRANZ APPRAISAL

Selected Premier Polyester Insulation products are BRANZ Appraised (Appraisal 1097 (2019)).

A BRANZ Appraisal is a robust, in-depth and independent evaluation of a building product or system to assess its fitness for purpose and compliance with Building Code performance requirements.

50 YEAR WARRANTY

PIL Group Limited takes pride in offering a 50-year Manufacturer's Durability Warranty for all Premier branded polyester thermal and acoustic insulation. This warranty assures the durability of the insulation material when installed in compliance with the product BRANZ Appraisal, the product Installation Instructions, and NZ4246: Energy Efficiency - Installing insulation in residential buildings.

ACOUSTIC PERFORMANCE

Premier 100% Polyester insulation will assist sound reduction by reducing the resonating noise inside the construction cavity. Performance will vary with different construction systems. The Premier brand offers a range of specialist 100% polyester acoustic products. Please visit our website for more information. For acoustic design assistance, please get in touch with our team.

Premier 100% Polyester R2.2 90mm Insulation has been independently assessed by Marshall Day Acoustics to verify it is a suitable sound control infill alternative in GIB® Noise Control® Systems. Refer: MDA LT 007 20221180 GE (PIL Polyester R2.2 90mm Testing and Verification).

INSTALLATION

It is recommended that all insulation be installed in accordance with the manufacturer's instructions and NZS:4246 Energy Efficiency - Installing Insulation in Residential Buildings. Please refer to individual product installation instructions available from our website.

Drained Cavity Wall Construction

Drained cavity wall construction with stud spacings greater than 450mm requires stud straps to prevent insulation bulging into the cavity. Straps must run at 300mm centres over the wall underlay. Refer NZBC E2/AS1, 9.1.8.5 Wall Framing behind Cavities.

Double-Layer Ceiling Installations

For higher R-Value ceiling installations we recommend a 'double-layer' installation to reduce thermal bridging and heat-loss through timber construction. Premier polyester will support multiple layers allowing performance flexibility. The bottom layer of insulation should be installed between the trusses. The second (top) layer should be installed tight around the trusses with joints off-set to the bottom layer of insulation. This will ensure a full cover of insulation and reduce heat-loss through timber construction.

Datasheet: Premier 100% Polyester Thermal Insulation Range

MATERIAL SAFETY DATASHEET

Premier 100% Polyester Insulation Material Safety Data Sheet is available from our website, or by contacting our Technical Team on 0800 467 855, or email support@premierinsulation.co.nz

CUSTOM MANUFACTURING

We offer simple product customisation to support specific project needs. Product width variations will require Minimum Order Quantity of 200m² per variant.

Please contact our Technical Team on 0800 467 855, or email support@premierinsulation.co.nz for more information.

PACKAGING & RECYCLING

Our Premier Polyester Insulation packaging is recyclable - made from LDPE 4 material.

Please refer to your local recycling centres for recycling options or contact PIL Group for information on our Take Back & Recycling options for plastic packaging and insulation off-cuts.

PROFESSIONALLY SUPPLIED & INSTALLED

Premier Insulation offers a nationwide installer network to help ensure our Premier 100% Polyester Insulation products are installed correctly and perform over the life of the building. Premier Insulation branches are locally owned and operated.

Find your local branch on our website.

SPECIFICATIONS & TECHNICAL SUPPORT

Premier specification documents are available from our website. For specification or technical support please contact our Technical Team on 0800 467 855, or email support@premierinsulation.co.nz



Appraisal No. 1097
Appraisal No. 1098



Licence No: 2517147

